



# Mine





# Mine

This luxurious flatwoven quality belongs to our Comfort Collection. A collection that consists only of soft, voluminous and elegant fabrics.

Mine is a real Textafoam evergreen. From the 1st launch it has been a well running quality in the Textafoam collection, and it still is. Over the years it grew further in volume and proved to be successful in almost every European country.

Mine is at this moment available in 38 trendy and commercial colours.

This micro chenille quality has been woven on an air jet loom, piece dyed and laminated with a 160 gram fleece backing. This heavy backing creates an even more thick and chunky handfeel to this popular upholstery fabric.

Mine is durable and easy to process on both fitted and loose fitting upholstery. It is an article that lasts for a very long period and is washable at 30 degrees (machine wash).

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

***Textafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

## Composition

/ faceside 96%PES 4%NY  
/ backside 100%PES  
/ chenille flatweave

## Suitable for


sofa's, beds, chairs with fitted and loose fitting upholstery




anthracite 67



army 14



azure 144



beige 05



brandy 127




brown 15



burgundy 34



caramel 16



chocolate 17



copper 126



coral 95




cream 02

Please note: colours may vary according to your screen settings.






denim 153




dolphin 180




eucalyptus 193



graphite 66



grey 65




hunter 156



khaki 51



lavender 71



lilac 70



lime 57




liver 10



magnolia 160


Please note: colours may vary according to your screen settings.




mandarin 129




mango 26




mustard 06



niagara 158



nightshade 178



petrol 56




pistachio 52



royalblue 47



sand 03



shell 196




sun 133




teal 198

Please note: colours may vary according to your screen settings.



white 104



yellow pastel 195

Please note: colours may vary according to your screen settings.

## Mine - Article passport

A luxurious flatwoven micro chenille quality with a thick and chunky handfeel.

Available from stock in a wide range of contemporary and commercial colours.

### Product characteristics

Productgroup	chenille flatweave
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery
Composition faceside	96%PES 4%NY
Composition backside	100%PES
Bonding	fleece
Statistic code	54076130
Dyeing method	piece dyed
Available colours	38
Packaging	transparent plastic

### Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	45.000		min. 8.000	min. 16.000	B
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	A
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	4-5		min. 4	min.5	B-C
	middle colours	CTL	grade	4-5		min. 4	min.5	B-C
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	dark colours	CTL	grade	4-5	4	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Ignitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

### Processing specifications

Minimum workable width in centimeters	± 138							
Roll length in meters	± 40							
Material weight in grams per linear meter	± 574							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	602	1.384	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	64,2	84,6	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	1,5	1,5	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	13,1	11,9	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

### Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	0,0	-0,8	n/a	n/a	A/A

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.



**Textaafoam**  
creativity in fabrics

Textaafoam b.v.  
La Défense 11 | 5026 SC Tilburg  
P.O. Box 12 | 5050 AA Goirle  
The Netherlands

T +31(0)13 534 5934  
F +31(0)13 534 7586  
E info@textaafoam.nl  
www.textaafoam.nl